

IDS-3110

10.4" SVGA Industrial Open Frame Monitor

NEW



Features

- 10.4" SVGA LCD panel with LED backlight for 20% power saving and environmental protection
- -20° C ~ +60° C wide range operating temperature
- 5-wire resistive touchscreen solution
- Combo touch interface: RS-232 and USB
- Dual signal interface with VGA & DVI
- Integrated bracket for easy installation
- Versatile mounting methods for rear mounting and VESA mounting
- Sunlight readable solution (optional)
- Ultra high brightness solution of 1200 cd/m² for outdoor application (optional)

Introduction

The Advantech IDS-3110 Embedded Open Frame Monitor series offers flexible options for LCD, touchscreen, signal interface and chassis mounting. The series supports rear and VESA mounting. The integrated brackets bring the benefits of easy installation and provide flexibility for different applications.


Specifications

| | | | |
|-------------|-----------------------|---|---|
| Display | Model | IDS-3110 | IDS-3110E |
| | Size | 10.4" LED panel | 10.4" LED panel |
| | Resolution | 800 x 600 (SVGA) | 800 x 600 (SVGA) |
| | Viewing Angle | 80°/80° (H), 60°/80° (V) | 80° /80° (H), 60° /70° (V) |
| | Brightness | 400 (cd/m ²) | 230 (cd/m ²) |
| | Color Support | 16.2M / 262K colors | 16.2M / 262K colors |
| | Contrast Ratio | 700:1 | 500:1 |
| | Response Time | 30 [msec] | 35 [msec] |
| | Backlight Life (hrs) | 50,000 hrs | 30,000 hrs |
| Touchscreen | Touchscreen Type | 5-Wire Resistive Touchscreen | |
| | Surface Hardness | 3H | |
| | Durability | 36 million touches | |
| | Transparency | 81%+/-3% | |
| Environment | Operating Temperature | -20 ~ 60° C (-4 ~ 140° F) | 0~ 45° C (32 ~ 113° F) |
| | Storage Temperature | -30 ~ 70° C (-22 ~ 158° F) | -20 ~ 60° C (-4 ~ 140° F) |
| | Humidity | 5 ~ 95% @ 40° C, non-condensing | |
| | Vibration | 5-500Hz, 0.026G ² /Hz, 2.16Grms, X, Y, Z 1 hour per axis | |
| System | I/O | VGA x 1; DVI-D x 1; 12 V _{DC} Jack x 1; USB x1; RS-232 x 1 (USB & RS-232 are reserved for the connection to enable touch usage only) | VGA x 1; 12 V _{DC} Jack x 1; USB x1; RS-232 x 1 (USB & RS-232 are reserved for the connection to enable touch usage only) |
| | OSD | Keys: Menu, Up, Down, Auto Adjust, Monitor Power on/off Menu Functions: Brightness, Contrast, Screen Settings, Color Temp, Language OSD Settings, VGA/ DVI , Recall , Auto Adjust | Keys: Menu, Up, Down, Auto Adjust, Monitor Power on/off Menu Functions: Brightness, Contrast, Color Adjust, Color Temp, Auto Color, and Language |
| | Power | 36 W power adapter, with AC 100 ~ 240 V input and DC +12 V @ 3 A output | |
| | EMC Compliance | CE/FCC/CCC | |


Dimensions

Unit: mm

IDS-3110 series



IDS-3110E series



Packing List

| Part Number | Description |
|-------------|--------------------------------------|
| 170002215 | 1 x M Cable USB-A(M)/USB-A(M) 180 cm |
| 1700151801 | 1 x VGA cable 15P(M) 1.8 meter |
| 1962055040 | 4 x clamper |
| 1935042520 | 4 x clamper screws M4_25L |
| 1992610005 | 1 x cable clamp |
| 1933030500 | 1 x cable clamp screw |
| 1992602010 | 1 x cable tie |
| 2066131100 | 1 x CD-ROM for IDS-3110 series |

* USB Cable is only included in IDS-3110R and IDS-3110ER series.

Note: Package contents are subject to change without prior notice

Optional Items

| Part Number | Description |
|-------------|---|
| 1700001524 | 3-pin power cord (US) |
| 170203183C | 3-pin power cord (EU) |
| 1700008921 | 3-pin power cord with PSE (Japan) |
| 1757003553 | Adapter 100-240V 36W 12V 3A W/O PFC 9NA |
| 1700000243 | DVI cable 2.0 meter |
| 1700091800 | Cable 9P/9P 1.8M M/F (Touchscreen RS-232 cable) |

Ordering Information

| Model Name | Description |
|--------------------|---|
| IDS-3110N-40SVA1E | 10.4" SVGA 400 cd/m ² LED Open Frame Monitor |
| IDS-3110R-40SVA1E | 10.4" SVGA 400 cd/m ² LED touch Touch Open Frame Monitor |
| IDS-3110EN-23SVA1E | 10.4" SVGA 230 cd/m ² LED Open Frame Monitor |
| IDS-3110ER-23SVA1E | 10.4" SVGA 230 cd/m ² LED touch Touch Open Frame Monitor |