

Touch Monitor

7" Touch Monitor



10.1" Touch Monitor



10.4" Touch Monitor



15.1" Touch Monitor



Model Name	7"	10.1"	10.4"	15.1"
Dimension	37.9H x 225.3W x 166.8D mm	38.6H x 293.4W x 210.4D mm	38.6H x 296W x 250.4D mm	40.5H x 404.1W x 335D mm
Case Material	ABS front frame + housing	ABS front frame + housing	ABS front frame + housing	ABS front frame + housing
Weight	1.1 Kg	1.8 Kg	2.1 Kg	4 Kg
Mounting Spec.	VESA 75	VESA 75	VESA 75	VESA 75
Panel Frame Water Proof	IP65	IP65	IP65	IP65
Optional Accessory	Wall Mount Kit / Stand	Wall Mount Kit / Stand	Wall Mount Kit / Stand	Wall Mount Kit / Stand
Max Resolution	1024 x 600	1280 x 800	1024 x 768	1024 x 768
Color Support	16.2M / 262K colors	16.2M / 262K colors	16.2M / 262K colors	16.2M / 262K colors
Max Sync Rate (V x H)	60 Hz x 80 kHz	60 Hz x 80 kHz	60 Hz x 80 kHz	60 Hz x 80 kHz
Response Time	10 ms (Falling time) 15 ms (Raising time)	10 ms (Falling time) 20 ms (Raising time)	11 ms (Falling time) 14 ms (Raising time)	2.3 ms (Falling time) 5.7ms (Raising time)
Touch Screen	ELCOM 4 wires Resistive Touch screen	AMT 5 wires Resistive Touch screen	AMT 5 wires Resistive Touch screen	AMT 5 wires Resistive Touch screen
Image Aspect Ratio	16:9	16:9	4:3	4:3
Brightness	500	300	350	450
Contrast Ratio	800:1	1300:1	1200:1	800:1
H-View Angle	150°	160°	176°	160°
V-View Angle	145°	140°	176°	150°
Signal Interfaces	VGA / DVI, USB Touch (COM Touch-Optional)	VGA / DVI, USB Touch (COM Touch-Optional)	VGA / DVI, USB Touch (COM Touch-Optional)	VGA / DVI, USB Touch (COM Touch-Optional)
Cables Included (Length: 1.8M)	VGA Cable x 1, USB Cable x 1	VGA Cable x 1, USB Cable x 1	VGA Cable x 1, USB Cable x 1	VGA Cable x 1, USB Cable x 1
Voltage Required	DC9~36V	DC9~36V	DC9~36V	DC9~36V
Power Consumption Operational	0.57A max.	0.57A max.	0.6A max.	1.02A max.
Operating Temperature	-20°C ~ 60°C	-20°C ~ 60°C	-20°C ~ 60°C	-20°C ~ 60°C
Operation Humidity Range	5~90% RH @ 39°C, non-condensing	5~90% RH @ 39°C, non-condensing	5~90% RH @ 39°C, non-condensing	5~90% RH @ 39°C, non-condensing
Storage Temperature	-30°C~+80°C	-30°C~+80°C	-30°C~+80°C	-20°C~+65°C
Storage Humidity Range	5~90% RH @ 39°C, non-condensing			