USB-4620 USB-4622 USB-4630

5-Port Isolated USB 2.0 Full-Speed Hub

5-Port USB 2.0 High-Speed Hub

4-Port Isolated USB 3.0 SuperSpeed™ Hub







Features

- 5 downstream USB 2.0 ports
- Supports USB 2.0 full speed
- 3,000 V_{DC} voltage isolation for each downstream port
- Suitable for DIN rail mounting
- One lockable USB cable included
- 10 ~ 30 V_{DC} power input (power adapter not included)

Features

- 5 downstream USB 2.0 ports
- Supports USB 2.0 high speed, USB 2.0 full speed, and USB 1.0
- 480 Mbps high-speed data transfer
- LED indicator
- Suitable for DIN rail mounting
- Lockable USB cable included
- 10 ~ 30 V_{DC} power input (power adapter not included)

Features

- external power source
- - Up to 5 Gbps transfer speed
- Lockable USB 3.0 cable is included

Specifications

Connectivity

- Ports
- Compatibility
- **Transfer Speed**
- Supply Current

1 x Upstream (Type B) 5 x Downstream (Type A) USB 2.0 full speed 12 Mbps 500 mA max. per channel

General

- Housing
- Dimensions (L x W x H)
- DC Input
- Power Consumption

- Operating Temperature Storage Temperature Storage Humidity non-condensing

Isolation Protection

Plastic (ABS+PC) 132 x 80 x 32 mm (5.2" x 3.15" x 1.26") 10 ~ 30 Vnc 24 V @ 36 mA

0 ~ 60 °C (32 ~ 140 °F) -20 ~ 70 °C (-4 ~ 158 °F) 5 ~ 95% RH

Protection

3,000 V_{DC}

Ordering Information

USB-4620-AE

5-port isolated USB 2.0 full-speed hub

Accessories

- 96PSD-A40W24-MM
- 1960004544 1960005788
- USB-LOCKCABLE-AE

DIN rail power supply, 40 W, 24 V Wall mount bracket VESA mount bracket Lockable USB 2.0 cable. 1 m, with screw kit

Specifications

Connectivity

- Ports
- Compatibility
- Transfer Speed
- Supply Current
- 5 x Downstream (Typé A) USB 2.0 high speed, USB 2.0 full speed, **USB 1.0** 480 Mbps/12 Mbps/1.5

General

- Housing
- Dimensions (L x W x H)
- DC Innut
 - **Power Consumption**
 - **Operating Temperature**
- **Storage Temperature** Storage Humidity

Plastic (ABS+PC) 132 x 80 x 32 mm (5.2" x 3.15" x 1.26") 10 ~ 30 Vpc 24 V @ 36 mA

1 x Upstream (Type B)

500 mA max. per channel

0 ~ 60 °C (32 ~ 140 °F) -20 ~ 70 °C (-4 ~ 158 °F) 5 ~ 95% RH

non-condensing

Ordering Information

USB-4622-BE

5-port USB 2.0

Accessories

- 96PSD-A40W24-MM
- 1960004544 1960005788
- USB-LOCKCABLE-AE

high-speed hub

DIN rail power supply, 40 W. 24 V Wall mount bracket VESA mount bracket Lockable USB 2.0 cable,

1 m. with screw kit

- 2,500 V_{DC} voltage isolation for upstream ports
- 4 x downstream USB 3.0 SuperSpeed™ ports
- Can be powered via a USB bus or 10 ~ 30 V_{DC}
- ESD protection up to ±8 kV (Level 3)
- Power status and downstream port speed LED
- The world's first isolated USB 3.0 SuperSpeed Hub

Specifications

Connectivity

- Ports
- Compatibility
- Transfer Speed Load Current
- 4 x Downstream (Type A) USB 3.0 SuperSpeed (1) 5 Gbps shared by all downstream ports External power: 900 mA max. per port USB bus power: 700 mA max. shared by all

ports (2)

1 x Upstream (Type B)

General

- Housing
- Dimensions (L x W x H)
- Power Input
- Power Consumption
- **Operating Temperature**
- Storage Temperature
- Storage Humidity
- 10 ~ 30 V_{DC} 760 mW (no load) 0 ~ 70 °C (32 ~ 158 °F) with external power 0 ~ 60 °C (32 ~ 140 °F) with USB bus power -20 ~ 70 °C (-4 ~ 158 °F)

Plastic (ABS + PC)

132 x 80 x 32 mm

(5.2" x 3.15" x 1.26")

Protection

- **Isolation Protection**
- **ESD Protection**

2,500 V_{DC} Contact discharge: ±4 kV (Level 2) Air discharge: ±8 kV (Level 3)

5 ~ 95% RH

(non-condensing)

Ordering Information

- 96PSD-A40W24-MM
- 96PS-A40WDIN

4-port isolated USB 3.0 SuperSpeed™ hub DIN rail power supply, 40 W, 24 V

AD\4NTECH |

Industrial I/O

All product specifications are subject to change without notice.