JBC141F9HG

Desktop Network Embedded Barebone N2930 / 4 or 8 Intel GbE / VGA / 12V



Features

- > Desktop Enetworking mbedded Barebone System
- > Intel Celeron N2930 Quad-Core SoC
- > Supports DDR3L-1333 SODIMM up to 8GB Total
- 2 * 2.5" SATA2 3Gb/s Internal Drive Bays
- > 1 * Full-size mSATA, 4 or 8 Intel Gigabit LAN Ports
- > 1 * Full-size mini-PCIE Slot (or WIFI installed)
- > 1 * USB 3.0 Port, 1 * USB 2.0 Port
- > 2 * Serial Ports (1 * RS232/422/485, 1 * RS232)
- VGA Port Installed, optional GPIO/COM cables included
- Watchdog Timer, 60W 12V AC Adapter
- Dimensions: 44 x 192 x 330mm

FRONT



(Shown with optional 2nd COM, GPIO, and 8-port LAN installed)

REAR



(Shown with optional WIFI antenna installed)

Model Part No HBJC141F9HG HBJC141F9HG04-29B (4-port, No WIFI), HBJC141F9HGW4-29B (4-port, WIFI) HBJC141F9HG08-29B (8-port, No WIFI), HBJC141F9HGW8-29B (8-port, WIFI) Processor Intel Celeron N2930 SoC Quad-core processor Memory 2 * 204-pin SO-DIMM slots supporting DDR31-1333 up to 8GB total Storage 2 * 2.5° SATA2 3Gb/s internal drive bays, 1 * Full-size mSATA slot Network 4 or 8 * Intel i211-AT Gigabit LAN 1 * Full-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model), SIM Card Holder Other Features AHCI, Watchdog Timer 10-255 min/sec., AT/ATX power mode support Rear Panel I/O Power switch 12V DC-in jack 2 * Antenna holes Grounding screw Front Panel I/O 1 * USB 3.0 1 * USB 3.0 1 * USB 2.0 Power LED, HDD LED 4 * RJ45, VGA 2 * DB9 punchout for COM/GPIO BIOS AMI UEFI 64Mb Flash ROM Box Contents 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 * 2dBl 2.4GHz Antenna on WIFI model) Compliance CE, FCC, RoHS, ErP Ready Temperature Operating Temperature 0 - 50° C
HBJC141F9HG08-29B (8-port, No WIFI), HBJC141F9HGW8-29B (8-port, WIFI) Processor
Processor Intel Celeron N2930 SoC Quad-core processor Memory 2 * 204-pin SO-DIMM slots supporting DDR3L-1333 up to 8GB total Storage 2 * 2.5" SATA2 3Gb/s internal drive bays, 1 * Full-size mSATA slot Network 4 or 8 * Intel i211-AT Gigabit LAN 1 * Full-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model), SIM Card Holder Other Features AHCI, Watchdog Timer 10-255 min/sec., AT/ATX power mode support Rear Panel I/O Power switch 12V DC-in jack 2 * Antenna holes Grounding screw Front Panel I/O 1 * USB 3.0 1 * USB 3.0 1 * USB 2.0 Power LED, HDD LED 4 * RJ45, VGA 2 * DB9 punchout for COM/GPIO BIOS AMI UEFI 64Mb Flash ROM Box Contents GOW 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 * 2dBl 2.4GHz Antenna on WIFI model) Compliance Cempliance
Memory
Storage 2 * 2.5" SATA2 3Gb/s internal drive bays, 1 * Full-size mSATA slot 4 or 8 * Intel i211-AT Gigabit LAN
Network 4 or 8 * Intel i211-AT Gigabit LAN 1 * Full-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model), SIM Card Holder Other Features AHCI, Watchdog Timer 10-255 min/sec., AT/ATX power mode support Rear Panel I/O Power switch 12V DC-in jack 2 * Antenna holes Grounding screw Front Panel I/O 1 * USB 3.0 1 * USB 3.0 1 * USB 2.0 Power LED, HDD LED 4 * RJ45, VGA 2 * DB9 punchout for COM/GPIO BIOS AMI UEFI 64Mb Flash ROM Box Contents 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 *2dBl 2.4GHz Antenna on WIFI model) Compliance Cempliance
Other Features AHCI, Watchdog Timer 10-255 min/sec., AT/ATX power mode support Rear Panel I/O Power switch 12V DC-in jack 2 * Antenna holes Grounding screw Front Panel I/O 1 * USB 3.0 1 * USB 2.0 Power LED, HDD LED 4 * RJ45, VGA 2 * DB9 punchout for COM/GPIO BIOS AMI UEFI 64Mb Flash ROM Box Contents 6 GW 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 *2dBl 2.4GHz Antenna on WIFI model) Compliance Ce, FCC, RoHS, ErP Ready
Other Features AHCI, Watchdog Timer 10-255 min/sec., AT/ATX power mode support Power switch 12V DC-in jack 2 * Antenna holes Grounding screw Front Panel I/O 1 * USB 3.0 1 * USB 2.0 Power LED, HDD LED 4 * RJ45, VGA 2 * DB9 punchout for COM/GPIO BIOS AMI UEFI 64Mb Flash ROM Box Contents 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 * 2dBI 2.4GHz Antenna on WIFI model) Compliance CE, FCC, RoHS, ErP Ready
Rear Panel I/O Power switch 12V DC-in jack 2 * Antenna holes Grounding screw Front Panel I/O 1 * USB 3.0 1 * USB 2.0 Power LED, HDD LED 4 * RJ45, VGA 2 * DB9 punchout for COM/GPIO BIOS AMI UEFI 64Mb Flash ROM Box Contents 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 * 2dBl 2.4GHz Antenna on WIFI model) Compliance CE, FCC, RoHS, ErP Ready
■ 12V DC-in jack ■ 2 * Antenna holes ■ Grounding screw Front Panel I/O ■ 1 * USB 3.0 ■ 1 * USB 2.0 ■ Power LED, HDD LED ■ 4 * RJ45, VGA ■ 2 * DB9 punchout for COM/GPIO BIOS ■ AMI UEFI 64Mb Flash ROM ■ 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 *2dBl 2.4GHz Antenna on WIFI model) Compliance ■ CE, FCC, RoHS, ErP Ready
Compliance 2 * Antenna holes Grounding screw Front Panel I/O 1 * USB 3.0 1 * USB 2.0 Power LED, HDD LED 4 * RJ45, VGA 2 * DB9 punchout for COM/GPIO BIOS AMI UEFI 64Mb Flash ROM 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 * 2dBl 2.4GHz Antenna on WIFI model) Compliance CE, FCC, RoHS, ErP Ready
Front Panel I/O 1 * USB 3.0 1 * USB 2.0 Power LED, HDD LED 4 * RJ45, VGA 2 * DB9 punchout for COM/GPIO BIOS AMI UEFI 64Mb Flash ROM Box Contents 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 *2dBl 2.4GHz Antenna on WIFI model) Compliance CE, FCC, RoHS, ErP Ready
Front Panel I/O 1 * USB 3.0 1 * USB 2.0 Power LED, HDD LED 4 * RJ45, VGA 2 * DB9 punchout for COM/GPIO BIOS AMI UEFI 64Mb Flash ROM 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 *2dBl 2.4GHz Antenna on WIFI model) Compliance CE, FCC, RoHS, ErP Ready
 1 * USB 2.0 Power LED, HDD LED 4 * RJ45, VGA 2 * DB9 punchout for COM/GPIO BIOS AMI UEFI 64Mb Flash ROM 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 *2dBl 2.4GHz Antenna on WIFI model) Compliance CE, FCC, RoHS, ErP Ready
 Power LED, HDD LED 4 * RJ45, VGA 2 * DB9 punchout for COM/GPIO BIOS AMI UEFI 64Mb Flash ROM 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 *2dBl 2.4GHz Antenna on WIFI model) Compliance CE, FCC, RoHS, ErP Ready
 4 * RJ45, VGA 2 * DB9 punchout for COM/GPIO BIOS AMI UEFI 64Mb Flash ROM 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 *2dBl 2.4GHz Antenna on WIFI model) Compliance CE, FCC, RoHS, ErP Ready
 2 * DB9 punchout for COM/GPIO BIOS AMI UEFI 64Mb Flash ROM Box Contents 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 *2dBl 2.4GHz Antenna on WIFI model) Compliance CE, FCC, RoHS, ErP Ready
BIOS AMI UEFI 64Mb Flash ROM Box Contents 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 *2dBl 2.4GHz Antenna on WIFI model) Compliance CE, FCC, RoHS, ErP Ready
Box Contents 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 *2dBl 2.4GHz Antenna on WIFI model) Compliance CE, FCC, RoHS, ErP Ready
cable, (2 *2dBl 2.4GHz Antenna on WIFI model) Compliance CE, FCC, RoHS, ErP Ready
Compliance ■ CE, FCC, RoHS, ErP Ready
Temperature ■ Operating Temperature 0 - 50° C
■ Storage Temperature -40 - 85° C
Dimensions ■ 192 x 330 x 44mm (DxWxH)
OS Support Windows 7, 8.1, 10, Linux
Warranty 2 Years limited warranty

^{*}Specifications subject to change without notice, not responsible for typographical errors. Does not include Memory, Storage or OS.



Jetway Computer Corporation
Phone: 510-857-0130 Fax: 510-857-0138
8058 Central Ave., Newark, CA 94560
www.jetwaycomputer.com

