

JBC142F791

Desktop Mini-ITX Embedded Barebone
Celeron 3955U / 2 GbE / 5 COM / RJ11



Features

- Desktop Embedded Barebone System with Planned Lifecycle Through Q3'2030
- Designed for POS or General Purpose PC
- Intel Celeron 3955U/3855U Dual-Core 15W
- Supports DDR4-2133 SODIMM up to 32GB Total
- Up to 2 Displays, HDMI, VGA
- 1 * 2.5" SATA3 6Gb/s Internal Drive Bay
- 1 * Full-size mSATA/Mini-PCIE Shared Slot
- 1 * Full-size mini-PCIE Slot (or WIFI Installed)
- 2 * Gigabit LAN, 4 * USB 3.0 Ports, 2 * USB 2.0 Ports
- 5 * Serial Ports (1 * RS232/422/485, 4 * RS232)
- Parallel, RJ11 for Cash Drawer (12V/24V), PS/2 Port
- Watchdog Timer, 60W 12V AC Adapter
- Dimensions: 44 x 192 x 330mm

Rear



Front



Model	<ul style="list-style-type: none"> ■ JBC142F791
Part No	<ul style="list-style-type: none"> ■ HBJC142791-3955B (Embedded CPU, No WIFI), HBJC142791W-3955B (Embedded CPU, WIFI) ■ HBJC142791-3855B (Non-Embedded, No WIFI), HBJC142791W-3855B (Non-Embedded, WIFI)
Processor	<ul style="list-style-type: none"> ■ 6th Gen Intel Celeron 3955U, 2.0GHz Dual-core, Embedded CPU, 15W, Skylake-U ■ 6th Gen Intel Celeron 3855U, 1.6GHz Dual-core, Non-Embedded CPU, 15W, Skylake-U ■ (CPU 40mm Fan, Chassis 1 * 40x20mm exhaust fan)
Memory	<ul style="list-style-type: none"> ■ 2 * 260-pin SO-DIMM slots supporting dual channel DDR4-2133 up to 32GB total
Storage	<ul style="list-style-type: none"> ■ 1 * 2.5" SATA3 6Gb/s internal drive bay, 1 * Full-size mSATA/Mini-PCIE shared slot
Network	<ul style="list-style-type: none"> ■ 2 * Realtek RTL8111H Gigabit LAN ■ 1 * Full-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model), SIM Card Holder
Other Features	<ul style="list-style-type: none"> ■ HD Audio, AHCI, Watchdog Timer 10-255 min/sec.
Rear Panel I/O	<ul style="list-style-type: none"> ■ 4 * USB 3.0 ports ■ 1 * HDMI 1.4 (4K @24Hz) ■ 1 * VGA ■ 2 * RJ45 ■ Line-out, Mic-in ■ 5 * Serial ports (1 * RS242/422/485, 4 * RS232) (1 * COM on MB, 4 * COM in accessory box) ■ Parallel port, RJ11 for cash drawer (12V/24V), PS/2 port ■ 2 * Antenna holes ■ 12V DC-In barrel jack (1-pin, 2.5mm ID/5.5mm OD)
Front Panel I/O	<ul style="list-style-type: none"> ■ Power, Reset, 2 * USB 2.0 ports
BIOS	<ul style="list-style-type: none"> ■ AMI UEFI 16MB Flash ROM
Box Contents	<ul style="list-style-type: none"> ■ 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, 4 * COM cables, GPIO cable ■ (2 * 2dBI 2.4GHz Antenna on WIFI model)
Compliance	<ul style="list-style-type: none"> ■ CE, FCC, RoHS, ErP Ready
Temperature	<ul style="list-style-type: none"> ■ Operating Temperature 0~50° C, Storage Temperature -20-85 ° C
Dimensions	<ul style="list-style-type: none"> ■ 192 x 330 x 44mm (DxWxH)
OS Support	<ul style="list-style-type: none"> ■ Skylake CPU: Windows 7, Windows 8.1, Windows 10, Linux ■ Kaby Lake CPU: 64bit Windows 10 UEFI, Linux UEFI
Warranty	<ul style="list-style-type: none"> ■ 2 Years limited warranty

*Specifications subject to change without notice, not responsible for typographical errors. Does not include Memory, Storage or OS.



Jetway Computer Corporation
Phone: 510-857-0130 Fax: 510-857-0138
8058 Central Ave., Newark, CA 94560
www.jetwaycomputer.com

