BC150F9N

1URackmount Embedded Barebone Celeron N2930 / up to 5 Intel LAN / HDMI

ALC: NO

Features

- Bay Trail M 1U Rackmount Embedded Barebone System \geq
- Planned Product Lifecycle Through Q1'2029 \triangleright
- \geq Intel Celeron N2930 1.83-2.16GHz SoC Quad-Core 7.5W
- Supports SO-DIMM DDR3L-1333 up to 8GB Total \geqslant
- ≻ 1 * Intel Gigabit LAN, Supports up to 5 Intel LAN Total
- \succ Supports 2 * 2.5" SATA Drives or 1 * 3.5" SATA Drive
- 1 * Full-size mSATA Slot, 1 * Full-size Mini-PCIE Slot \geq
- 1 * Serial, 2 * PS/2 Ports, HDMI, VGA, USB 3.0 \geq
- 200W FlexATX Power Supply \geq

Part No HBJC150F9N-2930-B (1*LAN), HBJC150F9N-2930BE (5*LAN)
Processor Intel Celeron N2930 SoC Quad-core 1.83GHz processor, 2.16GHz Burst, 7.5 TDP
Memory 2 * 204-pin DDR3L-1333 1.35V SO-DIMM up to 8GB total memory, 1.35V required
Expansion Slots 1 * Full-size Mini-PCIE slot, PCI Express x 1 slot (riser not included)
Storage 2 * 2.5" SATA2 drives (max 9.5mm height) or 1 * 3.5" SATA2 drive
1 * Full-size mSATA slot (shares 2 nd SATA port)
Network 1 * Intel i211-AT gigabit LAN, Supports up to 5 * Intel LAN by adding 1 * ADE4INLANG
Other Features ACPI S3, AHCI, Watchdog Timer 10-255 min/sec,
Rear Panel I/O 1 * USB 3.0 port, 3 * USB 2.0 ports, HDMI, VGA, 1 * RJ45, PS/2 Keyboard, PS/2 Mouse,
Antenna holes, AC Plug, Alternate power & reset button
Front Panel I/O Power & Reset button, Power & HDD LED, 2 * USB 2.0 ports
BIOS AMI 64MB SMT Flash ROM
Box Contents US Power Cord, SATA Cable, Manual, Driver disk, Mounting ears
Compliance CE, FCC, RoHS, ErP Ready
Temperature Operating Temperature 0~40 ° C, Storage Temperature -20-85 ° C
Dimensions 252 x 430 x 44mm (DxWxH)
Warranty 2 Years limited warranty *Specifications subject to change without notice, not responsible for typographical errors.



Jetway Computer Corporation Phone: 510-857-0130 Fax: 510-857-0138 8058 Central Ave., Newark, CA 94560 www.jetwaycomputer.com