

JBC511F9K Series

Thin Mini-ITX Fanless Embedded Barebone
Intel Celeron 1047 / Intel LAN / 4 COM

Features

- Fanless Embedded Barebone System with Planned Lifecycle Through Q1'2018
- Thin Fanless Black Aluminum Enclosure
- Intel Celeron 1047UE, 1.4GHz, Dual-Core, 17W
- Supports DDR3-1600 SODIMM up to 16GB Total
- Supports up to 2 Displays, HDMI, VGA
- 1 * 2.5" SATA3 6Gb/s Internal Drive Bay
- 1 * Full-size mSATA/mini-PCIE Shared Slot
- 1 * Intel Gigabit LAN, 7 * USB 2.0 Ports
- 4 * Serial Ports (1 * RS232/422/485, 3 * RS232)
- Watchdog Timer, 60W AC Adapter
- Includes Wall Mount Brackets
- Includes DIN Rail Kit and Clips
- Only 38 x 199.4 x 264mm
(1.5" x 7.85" x 10.39")



Model	<ul style="list-style-type: none"> ■ JBC511F9K
Part No	<ul style="list-style-type: none"> ■ HBJC511F9K-1047-B (non-WIFI) ■ HBJC511F9KW-1047-B (WIFI)
Processor	<ul style="list-style-type: none"> ■ Intel Celeron 1047UE, 1.4GHz Dual-Core mobile processor, 17W, Ivy Bridge
Memory	<ul style="list-style-type: none"> ■ 2 * 204-pin SO-DIMM slots supporting dual channel DDR3-1600 up to 16GB total
Storage	<ul style="list-style-type: none"> ■ 1 * 2.5" SATA3 6Gb/s internal drive bay ■ 1 * mSATA/mini-PCI Express shared slot (Full-size) ■ (802.11 b/g/n + BT 4.0 installed in WIFI model)
Network	<ul style="list-style-type: none"> ■ 1 * Intel i211AT Gigabit LAN
Other Features	<ul style="list-style-type: none"> ■ HD Audio, AHCI, Watchdog Timer 10-255 min/sec.
Rear Panel I/O	<ul style="list-style-type: none"> ■ 3 * USB 2.0 ports ■ 1 * HDMI ■ 1 * VGA ■ 1 * RJ45 ■ Line-out ■ 1 * Serial port (RS242/422/485) ■ 2 * Antenna hole ■ 9V - 24V DC In locking jack (1-pin 2.5mm ID, 5.5mm OD)
Front Panel I/O	<ul style="list-style-type: none"> ■ Power button, Reset button ■ 4 * USB 2.0 ports ■ 3 * Serial Ports (1 * RS232/422/485, 2 * RS232) ■ Line-in, Mic-in
BIOS	<ul style="list-style-type: none"> ■ AMI UEFI 32MB DIP Flash ROM
Box Contents	<ul style="list-style-type: none"> ■ 60W 12V AC Adapter, US Power Cord ■ Manual, DVD Driver disk ■ Wall + DIN Rail mounting brackets ■ DIN Rail Clips ■ Port dust covers ■ (Antennas on WIFI model)
Compliance	<ul style="list-style-type: none"> ■ CE, FCC, RoHS, ErP Ready
Temperature	<ul style="list-style-type: none"> ■ Operating Temperature 0~40 ° C, Storage Temperature -20-85 ° C
Dimensions	<ul style="list-style-type: none"> ■ 264 x 199.4 x 38mm (DxWxH)
OS Support	<ul style="list-style-type: none"> ■ 32/64 bit versions of Win 7, Win 8.1, Linux
Warranty	<ul style="list-style-type: none"> ■ 1 Year limited warranty

*Specifications subject to change without notice, not responsible for typographical errors. Does not include Memory, Storage or OS.



Jetway Computer Corporation
Phone: 510-857-0130 Fax: 510-857-0138
8058 Central Ave., Newark, CA 94560
www.jetwaycomputer.com

